

DISCO <sup>1</sup>		FRONT MOWERS													CONTOUR centrally hitched rear mowers								100 series side-mounted rear mowers						10 series side-mounted rear mowers		
		3600 FRC MOVE	3600 FC MOVE	3600 F MOVE	3200 FRC MOVE	3200 FC MOVE	3200 F MOVE	3600 FRC PROFIL	3600 FC PROFIL	3600 F PROFIL	3200 FRC PROFIL	3200 FC PROFIL	3200 F PROFIL	3150 F	4000 CONTOUR	3600 RC CONTOUR	3600 / 3600 C CONTOUR	3200 RC CONTOUR	3200 / 3200 C CONTOUR	2800 RC CONTOUR	2800 / 2800 C CONTOUR	360	320	320 C	280 RC	280 C	240 RC	32	28	24	
<b>Mower</b>		Front mowers													CONTOUR centrally hitched rear mowers								100 series side-mounted rear mowers						10 series side-mounted rear mowers		
Working width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.00	3.40	3.40	3.00	3.00	3.00	3.00	3.80	3.40	3.40	3.00	3.00	2.60	2.60	3.40	3.00	3.00	2.60	2.60	2.20	3.00	2.60	2.20	
Transport width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.40	3.40	3.40	3.00	3.00	3.00	3.00	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Machine height	m	–	–	–	–	–	–	–	–	–	–	–	–	–	3.90	3.57	3.57	3.19	3.19	2.86	2.86	3.80	3.40	3.50	3.10	3.10	2.70	3.50	3.10	2.70	
Weight (depending on conditioner)	approx. kg	1420	1390	1060	1250	1220	970	685	1195	870	1040	1010	775	685	1040	1300	950 / 1280	1180	870 / 1150	1070	810 / 1050	850	800	1130	1060	1040	980	750	700	650	
MAX CUT mower bed <sup>2</sup>		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Discs (2 knives per disc)		8	8	8	7	7	7	8	8	8	7	7	7	7	9	8	8	7	7	6	6	8	7	7	6	6	5	7	6	5	
Quick knife change		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	○	○	○	
Conditioner speed	rpm	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	–	–	940	– / 910	940	– / 910	940	– / 910	–	–	900	900	900	900	–	–	–	
Spring suspension		–	–	–	–	–	–	●	●	●	●	●	●	●	–	–	–	–	–	–	–	●	●	●	●	●	●	●	●	●	
ACTIVE FLOAT suspension		● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	
<b>Tractor requirements</b>																															
Hitch category		II	II	II	II	II	II	II	II	II	II	II	II	II	III	III	II / III	III	II / III	II	II	II	II	II	II	II	II	II / Quick hitch	II / Quick hitch	II / Quick hitch	
PTO shaft speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	540 (460)	540 (460)	540 (460)	540 (460)	540 (460)	540 (460)	
Hydraulic spool valves		1 x sa (+1 x da <sup>4</sup> + 1 x sa <sup>3</sup> )						(1 x da <sup>4</sup> + 1 x sa <sup>3</sup> )						1 x da <sup>5</sup> (+1 x da <sup>4</sup> + 1 x sa <sup>3</sup> )		1 x da <sup>5</sup> (+ 1 x sa <sup>3</sup> )				1 x da	1 x da	1 x sa	1 x sa	1 x sa	1 x sa	1 x sa	1 x sa	1 x sa			
<b>Equipment</b>																															
Hydraulically foldable protective side covers		○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	–	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Wide crop spreading		–	○	–	–	○	–	–	○	–	–	○	–	–	–	–	–/○	–	–/○	–	–/○	–	–	○	–	○	–	–	–	–	
Adjustable swathing plates		●	●	–	●	●	–	●	●	–	●	●	–	–	–	●	–/●	●	–/●	●	–/●	–	–	●	●	●	●	–	–	–	
Outside swathing disc		–	–	● (2 x)	–	–	● (1 x)	–	–	● (2 x)	–	–	● (1 x)	● (1 x)	○	–	○/–	–	○/–	–	○/–	○	○	–	–	–	–	○ <sup>7</sup>	○ <sup>7</sup>	○ <sup>7</sup>	
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Double high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Mower bed protection device (for intensive use)		○	○	○	○	○	–	○	○	○	○	○	–	–	–	○	–/○	○	–/○	○	–/○	–	–	–	–	–	–	–	–	–	
Illuminated warning signs		○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○ <sup>6</sup>	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Double mirror		○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Hydraulic transport locking device		–	–	–	–	–	–	–	–	–	–	–	–	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	
Mechanical collision protection		–	–	–	–	–	–	–	–	–	–	–	–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Storage frame		–	–	–	–	–	–	–	–	–	–	–	–	–	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Headland limit stop		–	–	–	–	–	–	–	–	–	–	–	–	–	●	●	●	●	●	●	●	○	○	●	●	●	●	○ <sup>8</sup>	○ <sup>8</sup>	○ <sup>8</sup>	

<sup>1</sup> C = tine conditioner, RC = roller conditioner, F = front, T = trailed, no suffix = without conditioner

<sup>2</sup> Standard mowing height 40 mm (continuously adjustable, 30–70 mm)

<sup>3</sup> 1 x sa required for setting the ACTIVE FLOAT pressure

<sup>4</sup> 1 x da required for the hydraulic folding of the protective cover

<sup>5</sup> With float position

<sup>6</sup> Folding

<sup>7</sup> Swathing plate with these models

<sup>8</sup> Hydraulic with these models

● standard ○ optional – not available

● standard ○ optional – not available

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.

	DISCO <sup>1</sup>	4000 TRC CONTOUR	4000 TC CONTOUR	3600 TRC CONTOUR	3600 TC CONTOUR	3200 TRC CONTOUR	3200 TC CONTOUR	3200 TC AUTOSWATHER	3150 TRC	3150 TC	3150 TC FLAPGROUPER
<b>Trailed mowers with CONTOUR central drawbar</b>									<b>Trailed mowers with side drawbar</b>		
<b>Mower</b>											
Working width	m	3.80	3.80	3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00
Transport width	m	3.80	3.80	3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00
Machine height	m	–	–	–	–	–	–	–	–	–	–
Weight (depending on conditioner)	approx. kg	2950	2420	2380	2320	2300	2230	2430	1900	1750	1900
MAX CUT mower bed <sup>2</sup>		●	●	●	●	●	●	●	●	●	●
Discs (2 knives per disc)		9	9	8	8	7	7	7	7	7	7
Quick knife change		●	●	●	●	●	●	●	●	●	●
Conditioner speed	rpm	1000	670	1140	1100 / 900	1140	1100 / 900	1230	1030	900 / 770	1030
Spring suspension		–	–	–	–	–	–	–	●	●	●
ACTIVE FLOAT suspension		●	●	●	●	●	●	●	–	–	–
<b>Tractor requirements</b>											
Hitch category		II / III	III	II	II	II	II	II	II	II	II
PTO shaft speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)
Hydraulic spool valves		1 x sa + 1 x da (+ 1 x sa <sup>3</sup> )						2 x sa + 1 x da (+ 1 x sa <sup>3</sup> )	1 x sa + 1 x da		
<b>Equipment</b>											
Hydraulically foldable protective side covers		–	–	–	–	–	–	–	–	–	–
Wide crop spreading		●	○	–	○	–	○	○	–	○	–
Adjustable swathing plates		●	●	●	●	●	●	●	●	●	●
Outside swathing disc		–	–	–	–	–	–	–	–	–	–
High-cut skids		○	○	○	○	○	○	○	○	○	○
Double high-cut skids		–	–	–	–	–	–	–	–	–	–
Wear skids		○	○	○	○	○	○	○	○	○	○
Mower bed protection device (for intensive use)		○	○	○	○	○	○	○	–	–	–
Illuminated warning signs		●	●	●	●	●	●	●	●	●	●
Double mirror		–	–	–	–	–	–	–	–	–	–
Hydraulic transport locking device		–	–	–	–	–	–	–	–	–	–
Mechanical collision protection		–	–	–	–	–	–	–	–	–	–

<sup>1</sup> C = tine conditioner, RC = roller conditioner, F = front, T = trailed, no suffix = without conditioner

<sup>2</sup> Standard mowing height 40 mm (continuously adjustable, 30–70 mm)

<sup>3</sup> 1 x sa required for setting the ACTIVE FLOAT pressure

<sup>4</sup> 1 x da required for the hydraulic folding of the protective cover

<sup>5</sup> With float position

<sup>6</sup> Folding

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.